





















IZALCO MAX DISC ULTEGRA DI2

Photo does not accurately represent specification



WHEEL SIZE	SIZE/CM	ARTICLE NO. EU	UK
28"	XXS/48	628 012 130	628 016 130
28"	XS/50	628 012 131	628 016 131
28"	S/52	628 012 132	628 016 132
28"	M/54	628 012 133	628 016 133
28"	L/56	628 012 134	628 016 134
28"	XL/58	628 012 135	628 016 135
28"	XXL/61	628 012 136	628 016 136

-  MAX technology carbon, disc, PF30 BB, 142x12 mm through axle, RAT Evo technology, Di2 ready, flat mount 140 mm, internal brake cable routing
-  MAX technology carbon, disc, 100x12 mm RAT through axle, RAT Evo Technology, flat mount 140 mm, internal brake cable routing
-  Shimano BT-DN110, internal Di2 Battery
-  EW-RS910 Bar-end A-Junction w/ EW-JC130 cable
-  Shimano Ultegra R8050, Di2, 11-speed, short cage
-  Shimano Ultegra R8050, Di2, braze on
-  Shimano Ultegra R8070, Di2
-  Shimano Ultegra R8000, 11-30T
-  Shimano Ultegra R8000, 52/36T
-  Pressfit
-  front: 52/36, rear: 11-30
-  Easton EA50, Aluminium, drop: 125mm, reach: 80 mm
-  BBB Deluxe, aluminium, 31.8 mm, +/- 7°
-  1-1/8", tapered, IS 47/33
-  Prologo Scratch STN Rail
-  BBB CPX Plus, Carbon, Di2 Ready, 27,2 mm, 350 mm, set-back: 20 mm
-  Shimano Ultegra R8070, disc, 160mm/160 mm
-  Shimano WH-RS770-C30, disc center-lock, carbon-alu, 100x12/142x12 mm, 24/24 spokes, 17 mm inner rim width
-  Continental GP4000S II, 700 x 25C, Folding
-  Candy Red